



NZJSA SELF-SCRUTINEERING FORM

Date:

Driver Name:

Boat #:

Class:

--	--	--	--

Area	Rule	Item	Comment	P/F
		Log book	Log book sited.	
Crew	2. (3).	Arm Restraints	Approved type, correct fit. Inspect condition.	
	2. (12).	Race suits	Approved type, correct fit. Inspect condition.	
	2. (12).	Balaclavas & Gloves	Approved type, correct fit. Inspect condition.	
	2. (14).	Helmets	Correctly fitting Snell approved 2010 (or higher) open face type. Inspect condition.	
	2. (15).	Frontal Head Restraints	Approved type, correct fit. Inspect condition.	
Trailer & Boat	2. (7).	Fire Extinguisher	Approved type, size & up-to-date.	
		Tow Fixture	Suitable for rescue towing.	
	1.1.1 1.2.1 1.2.2	Race Numbers	150mm, both sides of apex plate. (B – black on white, A – black on red, SB – white on black).	
Cockpit	2. (1). 2.1.5 (6).	Safety Harness	Approved type, under 5 years from manufacture date (date recorded in log book). Inspect condition of webbing, mounting points & release mechanism. Correctly anchored. Lock wired if applicable.	
	2.1 (3). 2.1.5 (8).	Seats	Correctly mounted.	
	2. (3a).	Head Restraints	Head correctly positioned.	
	2.1.3 (7).	Head Clearance	Minimum 100mm.	
	2. (3b).	Navigator Footrest	Correctly positioned.	
	2.1.7 (4).	Roll Cage Protective Padding	Adequately placed.	
	2. (5).	Ignition Isolating Switch	Correct location.	
	1.	Reverse	Operational from cockpit.	
	2. (10).	Throttle	Return springs.	
	2. (9).	Steering System	Guards on pulleys, cable condition, tensioners & chain lock wired.	
	2. (9).	Steering Column	Secure, no alloy shafts or extensions.	
Engine & Bay	1.	Engine Mounting	Suitable bolts, no visible cracks.	
	1.2.2	Mufflers	Fitted, meet specified DBA level.	
	2. (4).	Fuel Tank	Securely mounted, non-spill sealing cap fitted. Adequate breathers, non-return valve fitted. Compatible fuel lines, secured. Methanol boats – letter 'M' placed at rear on both sides, 150mm, red with white outline.	
		Driveshaft	Universals, suitable size, bolting & condition. GA – flat or angled up to engine.	
	2. (4).	Battery	Adequately restrained.	
	2.1 2.1.1 2.1.2 2.1.3 2.1.6	Roll cage	Correct specification & configuration, mounting brackets (size, thickness & backing plates), anchor points, bolt size & quantity, roll cage spread, crew protection maintained. Record green sheeting seal number in log book.	
		Engine Seals	Present in locations as per Engine Sealing Sheet.	
	1.2.1 1.2.2	Starting System	GB & GA – able to start under own power.	
Jet Unit	1.2.1 1.2.2	Steering	Correct size as per class rules. Nozzle pins, present and tight. Steering shaft & lock nut.	

Signature: (Driver)

Print Name: